



SLUXLUM

What is SLuxLum?

SLuxLum is SuppLux's signature luminaire series, featuring two product lines: CombiLight and All-in-One.

- **CombiLight** offers modular lighting built from profiles and LED strips—flexible for any design or custom project.
- **All-in-One** delivers fully integrated, plug-and-play luminaires for ultimate convenience.

Both series support all common installation types: Surface, Pendant, Wall, and Recessed.

With SLuxLum, you get versatile, ready-to-install lighting for every space.




All-in-One — Power Built In. Effortless Installation.

The driver is fully integrated inside the profile.

Comes with custom accessories for fast, tool-free setup.


Just snap, connect, and light up your space.











DIAL-UP CCT-SELECTED AND POWER-SELECTED LINEAR LIGHT

The purpose of the CCT-selected and power-selected linear fixture is to provide a flexible choice for users who can choose an appropriate color temperature and power freely as per their personalized favorite as well as reduce inventory and finance pressures for wholesalers & distributors to enhance their products turnover rate and marketing capacity. CCT-selected and power-selected version is applicable to various LED linear lights.


1. Reduce inventory quantity;
2. Humanization design;
3. One light to cover nine linear lights;
4. National Utility Patent;
5. Suitable for L5070C、L6870C.



Custom Shapes







All-In-One SL9086A










Feature

- Aluminum 6063-T5, 94-V2 PC matting diffuser;
- Ladder type structure design, convenient for assembly, disassembly and maintenance;
- Integrated diecast end cap, combine by screw and magnet;
- Straight connection and other 5 connection angles, easy assembly.



Standard

	Profile	L9086-PF
	End cap	L9086-DE
	Diffuser	W33-CV
	Safety cord	L4579-SR

Optional accessories


	Hexagonal screw driver L-IT		L Connector L9086-90L
	Disassembly tool L-DA		L Connector L9086-90W
	Driver		L Connector L9086-90N
	LED strip SMD420SC40BL		T Connector L9086-90T
	Carrier clip L9086-CC		X Connector L9086-90X
	Prismatic Diffuser W33-UGR		

Dimensions



Cutting

- Dimension of linear lighting fixture assembly




All-In-One SL9086A

Feature


- Non-dim, support 0~10V, DALI, Triac dimming solutions etc(optional);
- Aluminum 6063-T5, good heat radiation with long lifespan;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;
- High lighting efficiency, save energy;
- PF≥0.9;
- Environment humidity 40~70% RH;
- Operating Tem.: -20°C~+45°C;
- Storage Tem.: -40°C~+60°C;
- Degradable packaging;
- Long lifespan, >50000 hours (L70B10).

Spectroscopic data






Remark: Output data is from test result of 4ft PDM linear light fixture;
Tolerance +10%.


Flux out : 3107lm




	L9086-A45	L9086-A45S	L9086-A68	L9086-A68S	L9086-A90	L9086-A90S
Size	L1232mm(4.04ft)xW90mm(0.30ft)xH86mm(0.28ft)		L1841mm(6.04ft)xW90mm(0.30ft)xH86mm(0.28ft)		L2451mm(8.04ft)xW90mm(0.30ft)xH86mm(0.28ft)	
Power	45W (11.3w/ft)		68W (11.3w/ft)		90W (11.3w/ft)	
Lumen	4715~5000LM (1178~1250LM/ft)		7070~7500LM (1178~1250LM/ft)		9430~10000LM (1178~1250LM/ft)	
Cover	PDM (98°) / Prismatic (81°)					
CRI	85+					
CCT	3000K/ 3500K/ 4000K/ 5000K/ 6000K/ customization					
IP grade	IP 40					
Working Voltage	AC100~277V / 50~60Hz					
Max Input Current	6A					
Profile color	Silvery (RAL9006) / Black (RAL9004) / White (RAL9003)					




All-In-One SL9086A




Pendant




L-PTB




L-JB (optional)




L-PTB-NPF




L-PTB-PF2




Ceiling mounted




L-SM-CL




L4579-SM




Recessed




L9086-BI




Linkable



L79-180



P-SM-6ft



L-CH

L-PTB: pendant wires

L-JB : canopy

L-PTB-NPF : pendant wire + canopy without cable hole

L-PTB-PF2 : pendant wire + canopy with cable hole

L-SM-CL: surface mounted clip

L4579-SM: ceiling mounted bracket

L9086-BI: recessed bracket


L79-180: straight connector

P-SM-6ft: Input AC cable (current ≤ 6A)

L-CH: connection cable

More installation details, please read user manual.

Package




Type	Size(cm)	CBM(m³)	Remark	Diffuser	NW(Kg)	GW(Kg)
Carton	260(L)*11.5(W)*8(H)	0.024	1pcs/carton, 4cartons/bundle	PDM	6.80	8.20


Installation

Installation-drywall



Installation-brick wall





THANK YOU